

CANALKLER 250 S assembly



CANALKLER 250 S assembly

BUILDING & CONSTRUCTION

Applications

Sewer jetting and heavy duty, high pressure water cleaning.

Advantages

- Very low sliding resistance which allows: higher cleaning efficiency, reduction of cleaning time and therefore, reduction of fuel consumption.
- Longer lifespan thanks to the special cover compound with higher abrasion resistance.
- Better flexibility, even at low temperatures.
- Easy to handle and user friendly.
- Deformation resistance.
- Extra high strength and security due to aramide reinforcement.

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: aramide textile, braided.

Cover: SBR/NR, black, smooth. Very low sliding resistance.

Temperature range: -30 °C to +80 °C.

Standard/Approval

ZH 1/406 (Guidelines for fluid spray jets).

Couplings/Fittings

All hoses are assembled with BSP female/BSP male.

All assembled hoses are pressure tested at 375bar and have an unique hose number.

Complementary information

Delivered with test certificate on each factory assembled hose.

ID mm		Wall thickness mm		OD mm	Working pressure bar	Bursting pressure bar	Bending radius mm	Weight kg/m	Length m	Article number	Stock or min. order m
13	±0.5	6.3	±0.5	25,6	250.0	625	70	0.45	40	5014178	•
									60	5014179	•
									80	5014180	•
									100	5014916	•
								120	5014005	•	
19	±0.6	6.3	±0.5	31,6	250.0	625	90	0.61	40	5014181	•
									80	5014182	•
									100	5014459	•
								120	5014006	•	
25	±0.8	7.15	±0.5	39,3	250.0	625	100	0.9	40	5014183	•
									50	5014874	•
									80	5014184	•
									100	5014238	•
									120	5014007	•
									150	5014461	•
									160	5014185	•
									180	5014186	•
							200	5014520	•		
							240	5014733	•		
32	±1.0	7.8	±0.6	47,6	250.0	625	130	1.12	40	5014187	•
									80	5014188	•
									120	5014008	•
									150	5014466	•
									160	5014189	•
									180	5014190	•
						200	5014655	400			
38	±1.0	8.0	±0.8	54	250.0	500	155	1.35	120	5014009	•

±Upon availability.
* Tolerance on length: ± 1 % (ISO 1307 Standard)

Branding

Embossed branding

